

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 09/01/2016      Revision date: 09/01/2016      Supersedes: 09/01/2016      Version: 5.2

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product form	Mixture
Trade name	CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD
Product code	BU Chemicals

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

Hilti (Canada) Corp.  
 2360 Meadowpine Boulevard  
 L5N 6S2 Mississauga, Ontario - Canada  
 T +1905 8139200  
 1-800-363-4458 toll free - F +1 905 813 9009

**Supplier**  
 Hilti (Canada) Corp.  
 2360 Meadowpine Boulevard  
 L5N 6S2 Mississauga, Ontario - Canada  
 T +1905 8139200  
 1-800-363-4458 toll free - F +1 905 813 9009

**Department issuing data specification sheet**  
 Hilti AG  
 Feldkircherstraße 100  
 9494 Schaan - Liechtenstein  
 T +423 234 2111  
[chemicals.hse@hilti.com](mailto:chemicals.hse@hilti.com)

**1.4. Emergency telephone number**

Emergency number	Chem-Trec Tel.: 1 800 424 9300 (USA, PR, Virgin Islands, Canada) Tel.: 703 527 3887 (Other countries)
------------------	---

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GHS-CA classification**

Flam. Aerosol 1	H222
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
STOT SE 3	H335
STOT RE 2	H373
Full text of H statements : see section 16	

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

**2.2. Label elements**

**GHS-CA labelling**

Hazard pictograms (GHS-CA)



Signal word (GHS-CA)

Danger

Hazard statements (GHS-CA)

- H222 - Extremely flammable aerosol
  - H315 - Causes skin irritation
  - H317 - May cause an allergic skin reaction
  - H319 - Causes serious eye irritation
  - H332 - Harmful if inhaled
  - H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
  - H335 - May cause respiratory irritation
  - H351 - Suspected of causing cancer
  - H373 - May cause damage to organs through prolonged or repeated exposure
- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P211 - Do not spray on an open flame or other ignition source
- P251 - Do not pierce or burn, even after use
- P260 - Do not breathe spray
- P280 - Wear eye protection, protective clothing, protective gloves
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary statements (GHS-CA)

**2.3. Other hazards**

No additional information available

**2.4. Unknown acute toxicity (GHS-CA)**

No data available

**SECTION 3: Composition/information on ingredients**

Not applicable

Name	Product identifier	%	GHS-CA classification
4,4'-diphenylmethanediisocyanate, isomeres and homologues	(CAS No) 9016-87-9	40 - 60	Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
tris(2-chloro-1-methylethyl) phosphate	(CAS No) 13674-84-5	10 - 25	Acute Tox. 4 (Oral), H302
Dimethyl ether	(CAS No) 115-10-6	10 - 25	Not classified
Propane	(CAS No) 74-98-6	10 - 25	Flam. Gas 1, H220 Compressed gas, H280
Isobutane	(CAS No) 75-28-5	10 - 25	Flam. Gas 1, H220 Compressed gas, H280

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

Name	Product identifier	%	GHS-CA classification
Butane	(CAS No) 106-97-8	10 - 25	Flam. Gas 1, H220 Compressed gas, H280

Full text of hazard classes and H-statements : see section 16

**SECTION 4: First-aid measures**

**4.1. Description of first aid measures**

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Call a poison center or a doctor if you feel unwell.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms/injuries after inhalation	May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	Irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	Eye irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

Suitable extinguishing media Water spray. Dry powder. Foam. Carbon dioxide.

**5.2. Unsuitable extinguishing media**

No additional information available

**5.3. Specific hazards arising from the hazardous product**

Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.

**5.4. Special protective equipment and precautions for fire-fighters**

Protection during firefighting Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

No additional information available

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

**6.2. Methods and materials for containment and cleaning up**

Methods for cleaning up	Mechanically recover the product.
Other information	Dispose of materials or solid residues at an authorized site. After curing, the product can be disposed of with household waste.

**6.3. Reference to other sections**

For further information refer to section 8: "Exposure controls/personal protection"

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. May form flammable/explosive vapour-air mixture.
Hygiene measures	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

**7.2. Conditions for safe storage, including any incompatibilities**

Storage conditions	Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep cool.
Storage temperature	5 - 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight. Keep away from ignition sources.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**8.2. Appropriate engineering controls**

Appropriate engineering controls	Ensure good ventilation of the work station.
----------------------------------	--

**8.3. Individual protection measures/Personal protective equipment**

Personal protective equipment	Protective clothing. Safety glasses. Gloves.
-------------------------------	--



Hand protection	Protective gloves.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	In case of inadequate ventilation wear respiratory protection.
Environmental exposure controls	Avoid release to the environment.

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	Aerosol.
Colour	No data available
Odour	No data available
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point	Not applicable
Freezing point	No data available
Boiling point	< 35 °C
Flash point	< 0 °C
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Extremely flammable aerosol
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	No data available
Density	< 1.3 g/cm <sup>3</sup>
Solubility	No data available
Log Pow	No data available
Viscosity, kinematic	No data available
Viscosity, dynamic	No data available
Explosive properties	Pressurised container: May burst if heated.
Oxidising properties	No data available
Explosive limits	No data available

**9.2. Other information**

No additional information available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Reactivity	Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Heating may cause a fire or explosion.
Conditions to avoid	Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	No additional information available.

**SECTION 11: Toxicological information**

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

**11.1. Information on toxicological effects**

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Inhalation: Harmful if inhaled.

ATE CA (gases)	4500.00000000 ppmv/4h
ATE CA (vapours)	11.00000000 mg/l/4h
ATE CA (dust,mist)	1.50000000 mg/l/4h

<b>4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)</b>	
LD50 oral rat	> 10000 mg/kg (Rat; Literature study)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit; Literature study)

<b>Dimethyl ether (115-10-6)</b>	
LC50 inhalation rat (mg/l)	309 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	164000 ppm/4h (Rat; Literature study)

<b>Propane (74-98-6)</b>	
LC50 inhalation rat (mg/l)	513 mg/l/4h (Rat; Literature)
LC50 inhalation rat (ppm)	280000 ppm/4h (Rat; Literature)

<b>Isobutane (75-28-5)</b>	
LC50 inhalation rat (mg/l)	> 50 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	11000 ppm

<b>tris(2-chloro-1-methylethyl) phosphate (13674-84-5)</b>	
LD50 oral rat	2800 - 4200 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value; 1011-1824 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)

<b>Butane (106-97-8)</b>	
LC50 inhalation rat (mg/l)	658 mg/l/4h (Rat; Literature)
LC50 inhalation rat (ppm)	276000 ppm/4h (Rat; Literature)

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Suspected of causing cancer.
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified

<b>CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD</b>	
Vaporizer	Aerosol

**SECTION 12: Ecological information**

**12.1. Toxicity**

Ecology - general	May cause long lasting harmful effects to aquatic life.
-------------------	---

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

<b>4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)</b>	
LC50 other aquatic organisms 1	> 1000 mg/l (96 h)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)
<b>Dimethyl ether (115-10-6)</b>	
LC50 fish 1	3082 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	756.2 mg/l (48 h; Daphnia magna)
LC50 fish 2	> 1000 mg/l (96 h; Pisces)
EC50 Daphnia 2	> 4400 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	154.9 mg/l (96 h; Algae)
<b>Propane (74-98-6)</b>	
TLM fish 1	17.8 - 19.7,96 h; Pimephales promelas
Threshold limit algae 1	1.45 - 4.53,72 h; Algae
Threshold limit algae 2	8 mg/l (72 h; Algae)
<b>Isobutane (75-28-5)</b>	
Threshold limit algae 1	1.07 mg/l (Algae)
Threshold limit algae 2	7.15 mg/l (72 h; Algae)
<b>tris(2-chloro-1-methylethyl) phosphate (13674-84-5)</b>	
LC50 fish 1	98 mg/l (96 h; Pimephales promelas; GLP)
EC50 Daphnia 1	65 - 335 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	56.2 mg/l (96 h; Brachydanio rerio)
Threshold limit algae 1	73 mg/l (96 h; Selenastrum capricornutum; Growth rate)
<b>Butane (106-97-8)</b>	
TLM fish 1	1000 mg/l (96 h; Pisces)
Threshold limit other aquatic organisms 1	0.6 - 0.9,504 h; Daphnia magna
Threshold limit algae 1	0.88 - 1.76,Algae

**12.2. Persistence and degradability**

<b>4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)</b>	
Persistence and degradability	Not readily biodegradable in water. Hydrolysis in water. No (test)data on mobility of the substance available.
<b>Dimethyl ether (115-10-6)</b>	
Persistence and degradability	Not readily biodegradable in water. Non degradable in the soil. Not applicable (gas).
<b>Propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
<b>Isobutane (75-28-5)</b>	
Persistence and degradability	Inherently biodegradable. Biodegradable in the soil. Not applicable (gas).
<b>tris(2-chloro-1-methylethyl) phosphate (13674-84-5)</b>	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.
<b>Butane (106-97-8)</b>	
Persistence and degradability	Readily biodegradable in water.

**12.3. Bioaccumulative potential**

<b>4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)</b>	
BCF fish 1	1 (Pisces)
Bioaccumulative potential	Not bioaccumulative.
<b>Dimethyl ether (115-10-6)</b>	
Log Pow	0.10 (Experimental value; 0.07; QSAR; KOWWIN; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Propane (74-98-6)</b>	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Isobutane (75-28-5)</b>	
BCF fish 1	20 - 52 (Pisces; QSAR)

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

BCF other aquatic organisms 1	20 - 52 (Daphnia magna; QSAR)
Log Pow	2.8 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>tris(2-chloro-1-methylethyl) phosphate (13674-84-5)</b>	
BCF fish 1	0.8 - 4.6 (Cyprinus carpio; Test duration: 6 weeks)
Log Pow	2.59 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Butane (106-97-8)</b>	
Log Pow	2.89 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

**12.4. Mobility in soil**

<b>Dimethyl ether (115-10-6)</b>	
Surface tension	0.020 N/m (-40 °C)
<b>Propane (74-98-6)</b>	
Surface tension	0.016 N/m (-47 °C)
<b>Isobutane (75-28-5)</b>	
Surface tension	0.014 N/m (-10 °C)
<b>Butane (106-97-8)</b>	
Surface tension	< 0.1 N/m (0 °C)

**12.5. Other adverse effects**

GWPmix comment No known effects from this product.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Waste treatment methods Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 Waste disposal recommendations After curing, the product can be disposed of with household waste.

**SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

**14.1. UN number**

UN-No. (ADR)	1950
UN-No. (IMDG)	1950
UN-No. (IATA)	1950
UN-No. (ADN)	1950
UN-No. (RID)	1950

**14.2. UN proper shipping name**

Proper Shipping Name (ADR)	AEROSOLS
Proper Shipping Name (IMDG)	AEROSOLS
Proper Shipping Name (IATA)	Aerosols, flammable
Proper Shipping Name (ADN)	AEROSOLS
Proper Shipping Name (RID)	AEROSOLS
Transport document description (ADR)	UN 1950 AEROSOLS, 2.1, (D)



**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

Transport document description (IMDG) UN 1950 AEROSOLS, 2.1

**14.3. Transport hazard class(es)**

**ADR**

Transport hazard class(es) (ADR) 2.1  
 Danger labels (ADR) 2.1



**IMDG**

Transport hazard class(es) (IMDG) 2.1  
 Danger labels (IMDG) 2.1



**IATA**

Transport hazard class(es) (IATA) 2.1  
 Hazard labels (IATA) 2.1



**ADN**

Transport hazard class(es) (ADN) 2.1  
 Danger labels (ADN) 2.1



**RID**

Transport hazard class(es) (RID) 2.1  
 Danger labels (RID) 2.1

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)



**14.4. Packing group**

Packing group (ADR)	Not applicable
Packing group (IMDG)	Not applicable
Packing group (IATA)	Not applicable
Packing group (ADN)	Not applicable
Packing group (RID)	Not applicable

**14.5. Environmental hazards**

Dangerous for the environment	No
Marine pollutant	No
Other information	No supplementary information available

**14.6. Special precautions for user**

**- Overland transport**

Classification code (ADR)	5F
Special provisions (ADR)	190, 327, 344, 625
Limited quantities (ADR)	1I
Packing instructions (ADR)	P207, LP02
Mixed packing provisions (ADR)	MP9
Tunnel restriction code (ADR)	D

**- Transport by sea**

Special provisions (IMDG)	63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	SP277
Packing instructions (IMDG)	P207, LP02
EmS-No. (Fire)	F-D
EmS-No. (Spillage)	S-U
Stowage category (IMDG)	None
Stowage and segregation (IMDG)	Protected from sources of heat For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but 'Separated from' class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2.
MFAG-No	126

**- Air transport**

PCA packing instructions (IATA)	203
PCA max net quantity (IATA)	75kg
Special provisions (IATA)	A145, A167, A802

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812 CC; CF-F ECO; CF-I 50 ECO GV;CF 125-50; CF 125-5W50; CF 126-N; CF 126; CF ISO 750; CF-I 750 B2 (-SV);CF 116-45; CF F 600; CF 116; CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

**Safety Data Sheet**

according to the Hazardous Products Regulation (February 11, 2015)

**- Inland waterway transport**

Classification code (ADN)	5F
Special provisions (ADN)	19, 327, 344, 625
Limited quantities (ADN)	1 L
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP, EX, A
Ventilation (ADN)	VE01, VE04
Number of blue cones/lights (ADN)	1
Carriage prohibited (ADN)	No
Not subject to ADN	No

**- Rail transport**

Special provisions (RID)	190, 327, 344, 625
Limited quantities (RID)	1L
Packing instructions (RID)	P207, LP02
Carriage prohibited (RID)	No

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

**SECTION 15: Regulatory information**

**15.1. National regulations**

No additional information available

**15.2. International regulations**

No additional information available

**SECTION 16: Other information**

SDS Major/Minor	None
Date of issue	01/09/2016
Revision date	01/09/2016
Supersedes	01/09/2016

Full text of H-statements:

H220	Extremely flammable gas
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled

**CF-AS CJP; CF ISO 765; CF ISO 500+; CF-I ECO +; CS-F JS; CF 812  
CC; CF-F ECO; CF-I 50 ECO GV; CF 125-50; CF 125-5W50; CF 126-N;  
CF 126; CF ISO 750; CF-I 750 B2 (-SV); CF 116-45; CF F 600; CF 116;  
CF-JI; CF 812; CF 812 WD; CF-I 65 ECO; CF-I XTW WD**

## Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

---

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

SDS\_CA\_Hilti

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*